TRANSPORT



Treaty Series No. 6 (1996)

Amendments

to the International Convention for Safe Containers (CSC) 1972, as amended

[The Amendments entered into force on 1 January 1993]

Presented to Parliament by the Secretary of State for Foreign and Commonwealth Affairs by Command of Her Majesty January 1996

> LONDON : HMSO £1.10 net

AMENDMENTS¹ TO THE INTERNATIONAL CONVENTION FOR SAFE CONTAINERS (CSC) 1972², AS AMENDED

1 Amendments to Annex I of the CSC

.1 Amend regulation 1, 1(b) to read:

"On each container, all maximum gross weight markings shall be consistent with the maximum gross weight information on the Safety Approval Plate".

- .2 In regulation 1, delete 1(c).
- .3 In regulation 1, add a new 1(c) to read as follows:

"The owner of the container shall remove the Safety Approval Plate on the container if:

- the container has been modified in a manner which would void the original approval and the information found on the Safety Approval Plate, or
- the container is removed from service and is not being maintained in accordance with the Convention, or
- if the approval has been withdrawn by the Administration."
- .4 Delete the two last sentences of regulation 2, 2(d).
- .5 In regulation 2, delete 3(d).
- .6 Add a new chapter V as follows:

"CHAPTER V — REGULATIONS FOR APPROVAL OF MODIFIED CONTAINERS

Regulation 11

Approval of Modified Containers

The owners of an approved container that has been modified in a manner resulting in structural changes shall notify the Administration or an approved organization duly authorized by it of those changes. The Administration or authorized organization may require retesting of the modified container as appropriate prior to recertification."

2 Amendments to Annex II of the CSC

.1 In the description of test 1.(A) (Lifting from corner fittings), add the following sentence under "Internal loading":

"In the case of a tank-container, when the test weight of the internal load plus the tare weight is less than 2R, a supplementary load distributed over the length of the tank is to be applied to the container".

.2 In the description of test 1.(B) (Lifting by any other additional methods), add the following sentence under "Internal loading":

"In the case of a tank-container, when the test weight of the internal load plus the tare weight is less than 1.25R, a supplementary load distributed over the length of the tank is to be applied to the container".

²Treaty Series No. 40 (1979), Cmnd. 7535.

¹The amendments were adopted by the Maritime Safety Committee at its fifty-ninth session by Resolution MSC.20(59) of 17 May 1991.

Published by HMSO and available from:

HMSO Publication Centre

(Mail, fax and telephone orders only) PO Box 276, London, SW8 5DT Telephone orders 0171-873 9090 General enquiries 0171-873 0011 (queuing system in operation for both numbers) Fax orders 0171-873 8200

HMSO Bookshops

49 High Holborn, London, WC1V 6HB (counter service only) 0171-873 0011 Fax 0171-831 1326 68-69 Bull Street, Birmingham B4 6AD 0121-236 9696 Fax 0121-236 9699 33 Wine Street, Bristol, BS1 2BQ 0117 9264306 Fax 0117 9294515 9-21 Princess Street, Manchester, M60 8AS 0161-834 7201 Fax 0161-833 0634 16 Arthur Street, Belfast, BT1 4GD 01232 238451 Fax 01232 235401 71 Lothian Road, Edinburgh, EH3 9AZ 0131-228 4181 Fax 0131-229 2734 The HMSO Oriel Bookshop The Friary, Cardiff CF1 4AA 01222 395548 Fax 01222 384347

HMSO'S Accredited Agents (see Yellow Pages)

and through good booksellers

